

WHAT IS CLAIMED IS:

1) An assembly comprising a cigar rest portion which moves from a first stored position to a second open position.

2) The assembly of Claim 1 further comprising a divot repair tool.

3) The assembly of Claim 2 further comprising a ball marker which is removably coupled to said cigar rest portion.

4) The assembly of Claim 3 wherein said ball marker includes a magnetic material.

5) The assembly of Claim 4 wherein said cigar rest portion includes a magnetic material.

6) The assembly of Claim 5 wherein said cigar rest portion has a certain width, and wherein said ball marker has a certain diameter, said certain diameter of said ball marker is larger than said width of said cigar rest portion.

7) A golf tool assembly comprising:

a ground repair portion having a pair of spaced prongs;

a handle portion which is coupled to said ground repair portion, wherein said prongs project away from said handle portion, said handle portion including a pair of

members which project in a direction opposite to said prongs, and wherein said members define an opening within said handle portion, said opening having a certain width; and

a cigar rest portion which is disposed between and pivotally coupled to said members.

8) The assembly of Claim 7 wherein said cigar rest portion is generally hollow, said assembly further comprising a magnet which is disposed within said generally hollow cigar rest portion.

9) The assembly of Claim 8 wherein said handle portion further includes a first angular abutting edge, and wherein said cigar rest portion further includes a second angular abutting edge, said first and said second angular abutting edges being adapted to abut, effective to prevent said cigar rest portion from moving in a certain direction.

10) The assembly of Claim 9 further comprising a selectively removable ball marker, said selectively removable ball marker having a magnetic material therein, said ball marker further having a certain diameter.

11) The assembly of Claim 10 wherein said certain diameter of said ball marker is larger than said certain width of said opening.

12) The assembly of Claim 11 wherein said opening of said handle portion is generally U-shaped.

13) The assembly of Claim 7 wherein said opening of said handle portion is generally triangular in shape.

14) A golf tool assembly comprising:

a first generally U-shaped portion which projects in a first direction;

a second generally U-shaped portion which projects in a second direction, wherein said second generally U-shape portion is coupled to said first generally U-shaped portion, and wherein said first direction is opposite to said second direction;

a selectively movable portion which moves from a first closed position to a second open position, said selectively movable portion being pivotally coupled to said first generally U-shaped portion; and

a selectively removable portion having a relatively thin profile, said selectively removable portion being removably coupled to said selectively movable portion, and which abuts at least one portion of said first generally U-shaped portion while said selectively movable portion is in said first position.

15) The assembly of Claim 14 wherein said first generally U-shaped portion comprises:

a body portion having a first end and a second end;
a first side portion which is integrally formed with said body portion on said first end, said first side portion including an aperture;

a second side portion which is integrally formed with said body portion on said second end, said second side portion including an aperture, said first side portion being substantially parallel to said second side portion;
and

a first restrictive portion having a first certain angle, said first restrictive portion being formed upon said body portion and between said first and said second ends.

16) The assembly of Claim 15 wherein said second generally U-shaped portion is a divot repair tool, said divot repair tool being fixedly coupled to said body portion.

17) The assembly of Claim 16 wherein said selectively movable portion comprises:

a generally rectangular exterior having a top side, a bottom side, a left side, a right side, a front side, and a back side;

an aperture which is formed through said left and said right side, and which traverses through said selectively movable portion;

a generally hollow containment area which is formed within said selectively movable portion; and

a second restrictive portion having a second certain angle, said second restrictive portion being formed upon said bottom side, wherein said first restrictive portion of said body portion being designed to abut said second restrictive portion of said selectively movable portion.

18) The assembly of Claim 17 further comprising a first magnetic material, said first magnetic material being disposed within said generally hollow containment area of said selectively movable portion.

19) The assembly of Claim 18 wherein said selectively movable portion is disposed between said first and said second side portions of said body portion, such that said apertures of said first and said second side portions align with said aperture of said selectively movable portion, and such that said first restrictive portion abuts said second restrictive portion, said assembly further comprising a pin member, said pin member being disposed through said apertures, effective to movably couple said selectively movable portion to said body portion.

20) The assembly of Claim 19 wherein said magnetic material comprises a magnet.

21) The assembly of Claim 19 wherein said magnetic material comprises a metal material which is magnetically attracted to a magnet.

22) The assembly of Claim 19 wherein said relatively thin profile and selectively removable portion comprises a generally circular ball marker, said ball marker including at least one second magnetic material.

23) The assembly of Claim 22 wherein said at least one second magnetic material comprises a magnet.

24) The assembly of Claim 22 wherein said at least one second magnetic material comprises a metal which is magnetically attracted to a magnet.

25) The assembly of Claim 22 wherein said at least one second magnetic material comprises:

a magnet; and

a metal which is magnetically attracted to a magnet.

26) The assembly of Claim 23 wherein said at least one second magnetic material of said ball marker is magnetically and removably coupled to said first magnetic material of said selectively movable portion when said selectively movable portion is in said first position.

27) The assembly of Claim 26 wherein selectively movable portion moves to said second position only upon a selective

removal of said ball marker from said selectively movable portion.

28) The assembly of Claim 27 wherein said ball marker has a certain diameter and wherein said body portion and said first and second sides have a certain width, said certain diameter of said ball marker being substantially similar to said certain width of said body portion and said first and second sides.

29) The assembly of Claim 27 wherein said first position of said selectively movable portion abuts said first and said second restrictive portions, thereby preventing said selectively movable portion from moving to a third position.

30) The assembly of Claim 27 wherein said ball marker is magnetically and removably coupled to said front side of said generally rectangular exterior when said selectively movable portion is in said first position, thereby preventing said selectively movable portion from moving to said second and said third positions.

31) The assembly of Claim 30 wherein said back side of said exterior further comprises a ridge portion, said ridge portion abutting said first restrictive portion only when said selectively movable portion is in said second position.

32) The assembly of Claim 31 wherein said selectively movable portion is substantially perpendicular to said first and said second sides only when said selectively movable portion is in said second position.